



PGDQ2.MH14386 Marking and Labeling Systems - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Marking and Labeling Systems - Component

[See General Information for Marking and Labeling Systems - Component](#)

ART GIKEN (K K)

23-8 NISHIMAKADO

NUMAZU-SHI, SHIZUOKA 410-0871 JAPAN

MH14386

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Pressure-sensitive printed labels.						
1*10(b), 1*00(b), 1*01(b)						
	Acrylic paint	100	-	X	X	-
	Aluminum	100	-	X	X	-
	Anodized aluminum	100	-	X	X	-
	Galvanized steel	100	-	X	X	-
	Melamine paint	100	-	X	X	-
	Epoxy	80	-	X	X	-
	Epoxy paint	80	-	X	X	-
	Acrylonitrile butadiene styrene	60	-	X	X	-
	Polycarbonate	60	-	X	X	-
	Polyphenylene oxide/ether	60	-	X	X	-
	Polypropylene	60	-	X	-	-
	Polystyrene	60	-	X	X	-
	Polyvinyl chloride	60	-	X	X	-
	Unsaturated polyester - thermoset	60	-	X	X	-
2*10(c), 2*00(c), 2*01(c)						
	Acrylic paint	100	-40	X	-	-
	Aluminum	100	-40	X	-	-
	Anodized aluminum	100	-40	X	-	-
	Galvanized steel	100	-40	X	-	-
	Melamine paint	100	-40	X	-	-
	Acrylonitrile butadiene styrene	60	-40	X	-	-
	Polyphenylene oxide/ether	60	-40	X	-	-
2*10(c), 2*00(c), 2*01(c)						
	Acrylic paint	100	-40	X	X	-
	Aluminum	100	-40	X	X	-

Anodized aluminum	100	-40	X	X	-
Galvanized steel	100	-40	X	X	-
Melamine paint	100	-40	X	X	-
Acrylonitrile butadiene styrene	60	-40	X	X	-
Polyphenylene oxide/ether	60	-40	X	X	-
3*10(d), 23*00(d), 3*01(d)					
Acrylic paint	100	-40	X	X	-
Aluminum	100	-40	X	X	-
Anodized aluminum	100	-40	X	X	-
Galvanized steel	100	-40	X	X	-
Melamine paint	100	-40	X	X	-
Epoxy	80	-40	X	X	-
Epoxy paint	80	-40	X	X	-
Phenolic - Phenol Formaldehyde	80	-40	X	X	-
Acrylonitrile butadiene styrene	60	-40	X	X	-
Polycarbonate	60	-40	X	X	-
Polyphenylene oxide/ether	60	-40	X	X	-
Polypropylene	60	-	X	-	-
Polystyrene	60	-40	X	X	-
Polyvinyl chloride	60	-40	X	X	-
Unsaturated polyester - thermoset	60	-	X	-	-
4*10(e), 4*00(e), 4*01(e), 4*10(e), 4*00(e), 4*01(e)					
Acrylic paint	100	-40	X	X	-
Aluminum	100	-40	X	X	-
Anodized aluminum	100	-40	X	X	-
Galvanized steel	100	-40	X	X	-
Melamine paint	100	-40	X	X	-
Epoxy	80	-40	X	X	-
Epoxy paint	80	-40	X	X	-
Acrylonitrile butadiene styrene	60	-40	X	X	-
Polycarbonate	60	-40	X	X	-
Polyphenylene oxide/ether	60	-40	X	X	-
Polypropylene	60	-	X	-	-
Polystyrene	60	-40	X	X	-
Polyvinyl chloride	60	-40	X	X	-
Unsaturated polyester - thermoset	60	-40	X	X	-
5B00f					
Acrylic paint	100	-40	X	-	-
Aluminum	100	-40	X	-	-
Anodized aluminum	100	-40	X	-	-
Galvanized steel	100	-40	X	-	-

Melamine paint	100	-40	X	-	-
Epoxy	80	-40	X	-	-
Epoxy paint	80	-40	X	-	-
Acrylonitrile butadiene styrene	60	-40	X	-	-
Polycarbonate	60	-40	X	-	-
Polyphenylene oxide/ether	60	-40	X	-	-
Polypropylene	60	-	X	-	-
Polystyrene	60	-40	X	-	-
Polyvinyl chloride	60	-40	X	-	-
Unsaturated polyester - thermoset	60	-40	X	-	-
6@00(g), 6@10(g)					
Acrylic paint	100	-40	X	X	-
Aluminum	100	-40	X	X	-
Anodized aluminum	100	-40	X	X	-
Galvanized steel	100	-40	X	X	-
Melamine paint	100	-40	X	X	-
Epoxy	80	-40	X	X	-
Epoxy paint	80	-40	X	X	-
Polyphenylene oxide/ether	80	-40	X	X	-
Acrylonitrile butadiene styrene	60	-40	X	X	-
Phenolic - Phenol Formaldehyde	60	-40	X	X	-
Polycarbonate	60	-40	X	X	-
Polypropylene	60	-	X	-	-
Polystyrene	60	-40	X	X	-
Polyvinyl chloride	60	-40	X	X	-
Unsaturated polyester - thermoset	60	-40	X	X	-
AG-1, AG-1L					
Acrylic paint	100	-40	X	X	-
Aluminum	100	-40	X	X	-
Anodized aluminum	100	-40	X	X	-
Galvanized steel	100	-40	X	X	-
Melamine paint	100	-40	X	X	-
Epoxy	80	-40	X	X	-
Epoxy paint	80	-40	X	X	-
Phenolic - Phenol Formaldehyde	80	-40	X	X	-
Polyphenylene oxide/ether	80	-40	X	X	-
Acrylonitrile butadiene styrene	60	-40	X	X	-
Polycarbonate	60	-40	X	X	-
Polypropylene	60	-	X	-	-
Polystyrene	60	-40	X	X	-
Polyvinyl chloride	60	-40	X	X	-

	Unsaturated polyester - thermoset	60	-40	X	X	-
AG-2, AG-2L						
	Acrylic paint	100	-40	X	X	-
	Aluminum	100	-40	X	X	-
	Anodized aluminum	100	-40	X	X	-
	Galvanized steel	100	-40	X	X	-
	Melamine paint	100	-40	X	X	-
	Epoxy	80	-40	X	X	-
	Epoxy paint	80	-40	X	X	-
	Phenolic - Phenol Formaldehyde	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Acrylonitrile butadiene styrene	60	-40	X	X	-
	Polycarbonate	60	-40	X	X	-
	Polypropylene	60	-	X	-	-
	Polystyrene	60	-40	X	X	-
	Polyvinyl chloride	60	-40	X	X	-
	Unsaturated polyester - thermoset	60	-40	X	-	-
AG-3, AG-3L						
	Acrylic paint	100	-40	X	X	-
	Aluminum	100	-40	X	X	-
	Anodized aluminum	100	-40	X	X	-
	Galvanized steel	100	-40	X	X	-
	Melamine paint	100	-40	X	X	-
	Epoxy	80	-40	X	X	-
	Epoxy paint	80	-40	X	X	-
	Phenolic - Phenol Formaldehyde	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Acrylonitrile butadiene styrene	60	-40	X	X	-
	Polycarbonate	60	-40	X	X	-
	Polypropylene	60	-	X	-	-
	Polystyrene	60	-40	X	X	-
	Polyvinyl chloride	60	-40	X	X	-
	Unsaturated polyester - thermoset	60	-40	X	X	-
AG-4, AG-4L						
	Acrylic paint	100	-40	X	X	-
	Aluminum	100	-40	X	X	-
	Anodized aluminum	100	-40	X	X	-
	Galvanized steel	100	-40	X	X	-
	Melamine paint	100	-40	X	X	-
	Epoxy	80	-40	X	X	-
	Epoxy paint	80	-40	X	X	-

Polyphenylene oxide/ether	80	-40	X	X	-
Acrylonitrile butadiene styrene	60	-40	X	X	-
Phenolic - Phenol Formaldehyde	60	-40	X	X	-
Polycarbonate	60	-40	X	X	-
Polypropylene	60	-	X	-	-
Polystyrene	60	-40	X	X	-
Polyvinyl chloride	60	-40	X	X	-
Unsaturated polyester - thermoset	60	-40	X	X	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

(b) - May be replaced by numeral 25-250 denoting the thickness of the label stock

(c) - May be replaced by 50 denoting the thickness of the label stock.

(d) - May be replaced by numeral 25-100 denoting the thickness of the label stock.

(e) - May be replaced by numeral 25 or 50 denoting the thickness of the label stock.

(g) - May be replaced by numeral 80-110 denoting the thickness of the label stock.

* - May be replaced by letter A, B or C.

@ - May be replaced by letter A or B.

Marking: Company name or trademark **株式会社 アート技研, AR** and model designation.

Last Updated on 2015-05-15

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".